

## THE HONDA XR250





## **Available Colours**













## XR250 ENGINE

Туре	DOHC, single-cylinder, four-stroke, four-valves, air- cooled, oil radiator
Displacement	249 cc
Maximum power output	23.3 cv at 7,500 rpm
Maximum torque	2.42 kgl.m at 6,000 rpm
Transmission	Six speed
Starter	Electric
CAPACITIES	
Fuel	11.5 litres (3.7 litres reserve)
Engine Oil	1.8 litres
FRAME	
Type	Semi-double cradle
Front suspension / travel	Telescopic fork / 245mm
Rear suspension / travel	High seat: pro-link / 242mm Low seat: pro-link / 224mm
Front brake / diameter	Hydraulic disk / 240mm
Rear brake / diameter	Drum / 130mm
Front Tire	90/90 - 21 M/C 54S
RearTire	120/80 - 18 M/C 62S
Wheel	Aluminium
ELECTRIC SYSTEM	
Ignition	CDI (capacitor discharge ignition)
Battery	12V - 6Ah
Headlight	35 / 35 W - halogen bulb

## **DIMENSIONS - HIGH SEAT**

**DDB** SA 29232

LxWxH	2,147 x 845 x 1,203mm
Wheelbase	1,427mm
Ground clearance	281mm
Seat height	880mm
Dry weight	134 kg
DIMENSIONS - LOW SEAT	
LxWxH	2,130 x 845 x 1,166mm
Wheelbase	1,416mm
Ground clearance	242mm
Seat height	840mm
Dry weight	134 kg

Honda South Africa (Pty) Ltd reserves the right to change and modify equipment or specifications at any time without prior notice. The models illustrated in this brochure may show specifications for various markets and not specifically for South Africa. They may include optional equipment and accessories not fitted as standard. Subject to error. For precise information, please contact your Honda Dealership. © Honda South Africa (Pty) Ltd. Not to be reproduced wholly or in part without written permission from Honda SA.